

PRESSALIT®

Pressalit Zaga 314 Standard toilet seat incl. hinge in stainless steel

314001-UN9999 Item number

EAN:5708590299716

Pressalit Zaga. A seat with a retro-touch. Soft, rounded contours and smooth, shiny surfaces. The new hingelinks of nylon are invisibly mounted, leaving the inner sides of the seat and cover with an even, smooth surface. It not only looks good, it's also easy to clean.

Colour Black (RAL 9005)

Description

PRESSALIT toilet seat with cover, model "Zaga", art. no. 314 made of colour ingrained duroplast with UN9


univertical hinge


- centre distance: 155 mm - load - ring seat 240 kg

- with inlaid duroplast hinges for easier cleaning

- suitable for many universal toilets

- 10 year guarantee





A7358 A7356 A7203

A7156

A7056

A7050

Design type	Sandwich
Designer	Pressalit
Design year	2001



PRESSALIT.

Pressalit Zaga 314 Standard toilet seat incl. hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 3,0069 kg

Carton size 457x389x68 mm

Gross weight 3,4069 kg

Crate size 469x401x348 mm

Weight per crate 17,0345 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are

not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



PRESSALIT.

Pressalit Zaga 314 Standard toilet seat incl. hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

br>
In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Rv Tel.: +45 8788 8788 Fax: +45 8788 8789

PRESSALIT: