

PRESSALIT.

Product	Changing table, 800 x 900 mm, electrically height adjustable		
Item number	R8711000		
	VVS:777630010		
	NRF:7501909		
	EAN:5708590286181		
	HMI: 48861		
Colour	White max 1000 min 650		
Product description	Pressalit offers a wide range of daycare changing tables, both free-standing and wall-hung, in several sizes and models. The wall-hung tables are also available in versions where the worktop folds away, which are suitable for rooms with limited space. Of particular use to daycare facilities and kindergartens are the low start wall-hung changing tables, which can be lowered to a height that allows children to climb onto the worktop themselves. All types of daycare changing tables are available in versions with sanitary appliances and a choice of taps, with or without pull-out shower heads.		
	Wallhung changing table, 800 x 900 mm. With electric motor and transformer, height adjustable from 650 mm - 1000 mm, with wired hand control. Molded worktop, incl. 2 wire baskets. Materials: ABS plastics, synthetic acrylic and powder-lacquered steel. Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	350 mm		
Product capacity	Max load: 75 kg.		
Speed upwards	Speed up mm: 14 mm/s Speed down mm: 14 mm/s		
Noise level	48 dB		
Materials	Lifting unit and baskets: Powder-laquered steel. Worktop: ABS with acrylic.		
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height.		



PRESSALIT.

Product Item number	Changing table, 800 x 900 mm, electrically height adjustable R8711000		
Features	Easy-to-clean surfaces ensure optimum hygiene.		
Mains connection (V)	230		
Actuator (motor)	LA31 Deskline (Linak), 1500N, IPX1		
Control box	CBD6 (Linak), IP20		
Wired remote control	HB30 (Linak), IPX4		
Power consumption (maximum load)	Power consumption by maximum load, watt: 96 W Power consumption by standby: 0,1 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.		
	Changing table. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, a long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200		

surface coating may deteriorate.

after cleaning, as some materials may otherwise be discolored and stained, and the



PRESSALIT.

Product Item number	Changing table, 800 x 900 mm, electrically height adjustable R8711000
Declaration of conformity	CE UK MASK-ROHS This product complies with the relevant requirements of: - Council Directive 2006/42/EC on machinery - Council Directive 2011/65/EC on RoHS. For the UK: - The Supply of Machinery (Safety) Regulations 2008 - Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012



PRESSALIT®

Prod	luct
Item	numbe

Changing table, $800 \times 900 \text{ mm}$, electrically height adjustable

R8711000

Installation in different wall types

3 1	
Concrete >B25 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Brick >= Mz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Sand Lime Brick >= HIz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Aerated Concrete P4 V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product Item number	Changing table, 800 x 900 mm, electrically height adjustable R8711000		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
	Drywall (2 x 12,5 mm) water-resistant		
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>	

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com