

# PRESSALIT.

Product	PLUS handrail corner 762 x 1200 mm RT128000		
Item number	K1120000		
	VVS:777568400		
	NRF:6311228		
	RSK:8980584		
	EAN:5708590146379		
	HMI: 25427		
	NBS:N13:436		
Colour	White		
<b>D</b> . d. d. d			
Product description	PLUS handrails are high-quality products and they can be combined in countless ways and they provide the final touch to furnishing a functional and flexible bathroom. A reliable solution with many different options, which can easily lay the grounds for increased independence.		
	PLUS handrail, 33 mm, reversible right/left, A: 762 mm x B: 1200 mm, for fixed mounting.  The projection of 50 mm from the wall makes it easy to take hold of the rail. Inkl. wall rosette, which covers the fixings.  Material:Powder-coated aluminium, plastic.  Excl. mounting kit.		
Product capacity	Maximum load: 235 kg. When the handrail is loaded with 235 kg, each wall fastener is loaded with 56 kg. Handrails are tested with a 1.5 safety factor in accordance with the requirements in ISO 17966:2016.		
Materials	Basic material: Aluminium		
	Surface material: Polyester lacquer		
	Cover cap: Cycoloy plastic		
	Strap: Nylon (PA)		
Ergonomy	The 33 mm diameter enables the rail to be held comfortably and firmly. The projection of 50 mm from the wall makes it easy to take hold of the rail.		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		



# PRESSALIT®

Product	PLUS handrail corner 762 x 1200 mm			
Item number	RT128000			
Cleaning	Handrails ALU. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as			
	long as they are diluted according to the instructions on the container.  DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70%			
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro			
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.			
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the part must be wiped over with a damp cloth wrung out in clear water.			
Declaration of conformity	CE UK MDR This product is in compliance with all relevant requirements of: - Regulation (EU) 2017/745 on medical devices.  For the UK: - Medical Device Regulation (MDR) 2002 on medical devices.			



## PRESSALIT.

Product		
Item number		

PLUS handrail corner 762 x 1200 mm

RT128000


### Installation in different wall types



#### Concrete >B25

V8617 - Mounting kit, 12 screws  $\emptyset$ 5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






#### Solid Brick >= Mz12

V8617 - Mounting kit, 12 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.





#### Solid Sand Lime Brick >= Hlz12

V8617 - Mounting kit, 12 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






#### **Aerated Concrete P4**

V8667 - Mounting kit, 12 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.





## Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8617 - Mounting kit, 12 screws  $\emptyset$ 5 x 50 - plugs SX8. NB! Plugs are not needed.

To be ordered separately.





# PRESSALIT®

Product Item number	PLUS handrail corner 762 x 1200 mm RT128000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (12 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (12 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of	<b>A</b>
	fatal injury to persons and walls.	<u>!</u>

pressalit.com