

Product	PLUS handrail section 790 mm, incl. wall rosette and strap
Item number	RT332108
	VVS:777569328
	EAN:5708590153810
	NBS:N13:436
	RT330 - A = 365 RT331 - A = 662 A RT332 - A = 790
	RT333 - A = 1090
Colour	Dark blue (RAL 5011)
Product description	PLUS hand rail tube, with wall rosette and strop.
	Length 790 mm, diameter 33 mm. Requires other hand rail elements for installation.
	Please enquire for special hand rail solutions.
	Excl. mounting kit. See Technical datasheet (pdf) for information on fixings suitable for various wall
	types.
	PLUS hand rail tube, with wall rosette and strop.
	Length 790 mm, diameter 33 mm.
	Requires other hand rail elements for installation. Please enquire for special hand rail solutions.
	Materials: Powder-coated aluminium and plastics.
	Excl. mounting kit.
Product capacity	Maximum load: With a span up to 1000 mm: 210 kg
	With a span up to 1300 mm: 150 kg.
Materials	Basic material: Aluminium
	Surface material: Polyester lacquer
	Cover cap: Cycoloy plastic
	Strap: Nylon (PA)
Ergonomy	The 33 mm diameter enables the rail to be held comfortably and firmly. The
	projection of 50 mm from the wall makes it easy to take hold of the rail.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a
-	period of five years from the invoicing date.



Product Item number	PLUS handrail section 790 mm, incl. wall rosette and strap RT332108
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based or corrosive cleaners as it may result in the surface being damaged.



Product

Item number

PLUS handrail section 790 mm, incl. wall rosette and strap RT332108

Installation in different wall types

Concrete >B25 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
Solid Brick >= Mz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
Solid Sand Lime Brick >= HIz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
Aerated Concrete P4 V8665 - Mounting kit, 4 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.	CHILLIN accommond
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8. NB! Plugs are not needed. To be ordered separately.	



Product Item number	PLUS handrail section 790 mm, incl. wall rosette and RT332108	strap
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	
Research Provide Land		

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com