

# PRESSALIT.

### Pressalit 718 Toilet seat with lift-off and soft close incl. hinge in stainless steel

Features Lift-off, Soft close

718000-D59999

EAN:5708590297200

Pressalit 718 is a universal toilet seat with soft close and lift-off for easy cleaning. The toilet seat is particularly

suited to building projects.

Colour White

**Description**PRESSALIT toilet seat with cover, model "Pressalit 718", art. no. 718 made of colour ingrained duroplast


with stainless steel hinges with lift-off with D59 universal hinge in stainless steel.


- centre distance: 112-197 mm

- load - ring seat 180 kg

- suitable for many universal shaped toilets

- 10 year guarantee







Design typeSandwichDesignerPressalitDesign year2011



# PRESSALIT.

#### Pressalit 718

Toilet seat with lift-off and soft close incl. hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even loss following curing

formaldehyde and even less following curing.

**BUFFERS**:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 180 kg

Weight 1,908 kg

Carton size 457x389x68 mm

Gross weight 2,338 kg

**Crate size** 469x401x348 mm

Weight per crate 11,69 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid

contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



# PRESSALIT.

### Pressalit 718 Toilet seat with lift-off and soft close incl. hinge in stainless steel

#### Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.<br/>

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

**PRESSALIT**