



# PRESSALIT®

<b>Product</b> <b>Item number</b>	MATRIX CURVE II ergonomic sink with tap hole and overflow R2052000
<b>Color</b>	VVS:636862300 NRF:6132513 RSK:7503001 EAN:5708590333861 HMI: 101015 White
<b>Product description</b>	<p>MATRIX is a series of sinks, most of them are designed by Pressalit. MATRIX SMALL and CURVE sinks fit onto PLUS, SELECT and VALUE sink brackets, whereas MATRIX MEDIUM and ANGLE are tailor made to fit specific brackets.</p> <p>MATRIX CURVE II ergonomic sink, 23.6" x 19.2" x 5.9", with tap hole diameter 1.4" and overflow. Supplied with drain fitting. The concave front edge stabilises standing as well as seated users. The rounded edges are also comfortable to hold and rest against. The flat bottom leaves room for the legs underneath. Material: Ceramic. Suitable for sink brackets from the Pressalit PLUS, SELECT and VALUE ranges.</p>
<b>Product capacity</b>	330 lbs.
<b>Materials</b> <b>Ergonomy</b>	Ceramic  The concaved front edge stabilizes a standing as well as a seated user. The rounded shapes are nice to grip and lean against. The design of the corners leaves space and supports the elbows in the sink and the flat bottom leaves space for the legs of a seated user.
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



PRESSALIT®











<b>Product</b> <b>Item number</b>	MATRIX CURVE II ergonomic sink with tap hole and overflow R2052000
<b>Cleaning</b>	<p>For cleaning the wash basin, use hot water and a mild soapy cleaning agent. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after cleaning.</p> <p>For disinfecting the wash basin, the following agents can be used:</p> <p>Sodium hydroxide 5% Acetic acid solution 10% Ethanol solution 70% Sodium hypochlorite 5%, active chlorine Sodium chloride 170g/l, diluted to 50%.</p> <p>Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after disinfection.</p> <p><b>NB! Do not use abrasive cleaning agents, as this will cause damage to the surface of the wash basin.</b></p>
<b>Declaration of conformity</b>	<p><b>Declaration of Performance</b></p> <p>Compliance criteria according to EN 14688:2015.</p> <p>4.1 Load resistance: Pass. 4.2 Draining of water: Pass. 4.3 Resistance to temperature changes: Pass. 4.4 Resistance to chemicals and staining agents: Pass. 4.5 Surface stability / resistance to scratching: Pass. 4.6 Cleanability: Pass. 4.7 Protection against overflow: CL 15. 4.8 Durability: Pass.</p>









PRESSALIT®

<b>Product</b>	MATRIX CURVE II ergonomic sink with tap hole and overflow
<b>Item number</b>	R2052000

## Mounting in different wall types

	<p><b>Concrete &gt;B25</b></p> <p>V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12. To be ordered separately</p>	
	<p><b>Solid Brick &gt;= Mz12</b></p> <p>V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12. To be ordered separately</p>	
	<p><b>Solid Sand Lime Brick &gt;= Hlz12</b></p> <p>V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12. To be ordered separately</p>	
	<p><b>Aerated Concrete P4</b></p> <p>V8652 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs GB14. To be ordered separately.</p>	
	<p><b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood</b></p> <p>V8602 - Mounting kit, 2 countersunk bolts Ø10 x 80, plugs SX12. NB! Plugs are not needed. To be ordered separately.</p>	



Product Item number	MATRIX CURVE II ergonomic sink with tap hole and overflow R2052000
	<b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood</b> Mounting in this wall type is not recommended - risk of fatal injury to persons and walls. 
	<b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)</b> Mounting in this wall type is not recommended - risk of fatal injury to persons and walls. 
	<b>Drywall (2 x 12,5 mm) water-resistant</b> Mounting in this wall type is not recommended - risk of fatal injury to persons and walls. 

It is the responsibility of the installer to ensure that suitable wall fasteners are used.