

PRESSALIT.

Product	PLUS shower seat 450, electrically height sideways adjustable	t adjustable and manually
Item number	R7664000	
	VVS:777517400	280
	NRF:6317153	
	EAN:5708590360263	385
	HMI: 124227	858
Colour	White	450 437
Product description	PLUS shower seats are offered in a number of fixed height, electrically adjustable and manual aperture, and with an option of back and armre They are suitable for wall-mounting or for fitting	ly adjustable, with and without ests.
	Powered PLUS shower seat 450, with back- ar adjustable by 500 mm and manually sideways independently height adjustable. The seat and Materials: Comfortable polyurethane foam over profile. The non-slip gripping surface of the arn For fitting to horizontal PLUS wall track (not income	adjustable, the armrests are the armrests are foldable. r a plywood core, fitted to an aluminium nrests are made of soft SEBS.
Adjustability	Height and sideways adjustable	
Adjustment height	500 mm	
Product capacity	Maximum user mass (seat): 150 kg. Maximum load for armrests is 55 kg. When the seat is loaded with 150 kg, each wall fastener is loaded with 35 kg.	
	The seat has been tested statically with safety according to the applied assistive products state	
Speed upwards	Speed up mm: 10 mm/s Speed down mm: 10 mm/s	
opoou upwarao	Speed down mm: 10 mm/s	



PRESSALIT.

Product	PLUS shower seat 450, electrically height adjustable and manually sideways adjustable	
Item number	R7664000	
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with an in-mould coated surface that is protected using a clear PU lacquer. The backrest is made of polyurethane (PU) foam protected using a clear PU lacquer. The arms are primarily constructed of 10-micrometre anodized aluminium, with a nor slip gripping surface at the end made of soft SEBS and inforporating a glass-reinforced nylon core. The hinge arm is also made of soft SEBS. Internal component and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.	
Ergonomy	Ergonomically designed seat - contact surface are 450 x 437 mm. Soft and slip-resistant material that has a warm feel. The oval shape of the armrests gives an eas and comfortable surface to lean on and push against.	
Features	Powered raising or lowering at the push of a button - the seat can easily be adjusted upwards or downwards to a good working height for the carer while the user sits on in The seat, backrest and armrests can be adjusted simultaneously thanks to a safe and easy click system. The armrests can also be adjusted independently of the seat and backrest. The seat and armrests can fold up when not in use or to maximise floor space. Wired hand control comes with brackets for fitting to the wall.	
Mains connection (V)	230	
Actuator (motor)	LA40 (Linak) 6000N, IPX6	
Control box	SMPS14 (Linak) IPX6	
Wired remote control	HB3 (Linak) IP66	
Power consumption (maximum load)	Power consumption by maximum load, watt: 60 W Power consumption by standby: 0,5 W	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



PRESSALIT.®

Product	PLUS shower seat 450, electrically height adjustable and manually sideways adjustable
Item number	R7664000
Cleaning	
3	PLUS shower seat.
	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS:
	Erisan OXY+ Tvättsprit 70%
	CaviCide surface disinfectant decontaminant cleaner
	Rodalon Desinfektionsspray Terralin protect (SCHÜLKE+)
	Dismonzon Plus (BODE Chemie GmbH)
	NON-DISINFECTANTS:
	Wetrok Caledor (Wetrok) Petrosol Citro (Büfa)
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anything other than soap and water.
	The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.
Declaration of conformity	CE MDR-MASK-RoHS This product is in compliance with all relevant requirements of a Regulation (EU) 2017/745 on medical devices - Council Directive 2006/42/EC on machinery - Council Directive 2011/65/EC on RoHS.



PRESSALIT®

PLUS shower seat 450, electrically height adjustable and manually sideways adjustable

Item number R7664000

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com