

| Product | INDIVO lift for countertop 78.8" - 94.5" | | |
|---------------------|--|--|--|
| Item number | RK1853202 | | |
| | EAN:5708590379111 | | |
| Color | Gray (RAL 9006) | | |
| Product description | The name INDIVO relates to the individual configuration of the products. Lifts are available for countertops of any length between 23.6" and 111.8". | | |
| | INDIVO lift for countertop, with three motors and control box. Max. load: 330 lbs including the countertop. Incl. cross brace and four brackets. Height adjustable up to 11.8" with switch or wired remote control. For countertop length 78.8" - 94.5". Please indicate length and depth of countertop when ordering. Excl. mounting kit. | | |
| Adjustability | Height adjustable | | |
| Adjustment height | 11,82 inch | | |
| Product capacity | Maximum load: 330 lbs, this includes the weight of the countertop. The load must be evenly distributed. | | |
| Speed up | Speed up: 0,79 inch/s Speed down: 0,79 inch/s | | |
| Noise level | 45 dB | | |
| Materials | Lifting columns: Powder-coated steel Cross brace: Aluminium Brackets: Powder-coated steel | | |
| Ergonomy | An electric height-adjustable kitchen countertop is ideal in all situations where various users - both seated and standing - use the same kitchen. This is equally true in private homes as well as larger centers with common kitchen facilities such as group homes and care centers. | | |



| Product | INDIVO lift for countertop 78.8" - 94.5" | | |
|----------------------------------|--|--|--|
| Product | | | |
| Item number | RK1853202 | | |
| Features | Lifts are height adjusted either via switches in the front edge or with a wired remot control. | | |
| Actuator (motor) | DL17 Deskline (Linak) 70N, IP22 | | |
| Control box | CBD6S (Linak) IP22 | | |
| Wired remote control | HB53 (Linak), IPX1 | | |
| Power consumption (maximum load) | Power consumption by maximum load: 300 W Power consumption by standby: 2 W | | |
| Warranty | Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. | | |



| Product | INDIVO lift for countertop 78.8" - 94.5" | | |
|---------------------------|---|--|--|
| Item number | RK1853202 | | |
| Cleaning | This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. | | |
| | The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. | | |
| | DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: | | |
| | Suma Star free D1 Taski 100 Taski 200 Milizid Citro | | |
| | The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. | | |
| | DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water. | | |
| Declaration of conformity | This product is solely intended for the US and Canada, and has no EU declaration of conformity. | | |



Product

INDIVO lift for countertop 78.8" - 94.5"

Item number

RK1853202


Mounting in different wall types


| a. V | í |
|---------------------------------------|---|
| .C | L |
| D a a a a a | L |
| · · · · · · · · · · · · · · · · · · · | L |
| O. S.D. X. G | L |
| . a · . V : [[· · · · · · · ·] | ı |

Concrete >B25

V8607 - Mounting kit, 9 lag bolts Ø 0.4" x 2.8" (Ø10 x 70 mm), plugs SX12.

To be ordered separately.







Solid Brick >= Mz12

V8607 - Mounting kit, 9 lag bolts Ø 0.4" x 2.8" (Ø10 x 70 mm), plugs SX12.

To be ordered separately.






Solid Sand Lime Brick >= Hlz12

V8607 - Mounting kit, 9 lag bolts Ø 0.4" x 2.8" (Ø10 x 70 mm), plugs SX12.

To be ordered separately.






Aerated Concrete P4

V8657 - Mounting kit, 9 lag bolts M0.4" x 2.8" (\emptyset 10 x 70 mm), plugs GB14.

To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8607 - Mounting kit, 9 lag bolts Ø 0.4" x 2.8" (Ø10 x 70 mm), plugs SX12. NB! Plugs are not needed.

To be ordered separately.





PRESSALIT®

| Product Item number | INDIVO lift for countertop 78.8" - 94.5" RK1853202 | |
|------------------------|---|--|
| | Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (9 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar. | |
| | Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (9 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar. | |
| | Drywall (2 x 12,5 mm) water-resistant Wall fasteners (9 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar. | |

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com